

HISTORIC SPORTS CAR CLUB LTD
Silverstone Circuit. Silverstone. Nr Towcester. Northamptonshire. NN12 8TN
Tel: +44 (0)1327 858400. .

E-mail: office@hsc.org.uk. Web Site: www.hsc.org.uk.

HSCC 105 Cup Series Regulations 2026

1. SPORTING REGULATIONS - GENERAL

1.1 Title and Jurisdiction:

The 105 Cup© is organised and administered by The Historic Sports Car Club [HSCC] in accordance with the National Competition Rules (NCR) (incorporating the provisions of the International Sporting Code of the FIA) and these Series Regulations.

Motorsport UK Series Registration No. RS2026/055

Race Status: Interclub

A Series registered in the UK is defined as a series of individual Events organised to a common set of Sporting and or Technical Regulations. There can be no accumulative overall or Class winner(s) or title awards based on the finishing positions drawn from a number of different Event results.

This document defines the specific Series regulations and structure of the Series for both fair and safe competition and are to be adhered to by all Entrants and Drivers at all times.

The Organisers reserve the right to amend or clarify these Series Regulations at any time during the season by way of publication of Official Series Bulletins issued in accordance with NCR Ch. 3 App. 10 Art 4.1 and subject to Motorsport UK approval.

1.2 Officials:

1.2.1 Series Coordinator : Donna Peters c/o HSCC Ltd, Silverstone Circuit, Silverstone Nr Towcester, Northants, NN12 8TN. Tel. 01327 858400

1.2.2 Series Eligibility Scrutineer: Sue Bateman c/o HSCC Ltd, Silverstone Circuit, Silverstone Nr Towcester, Northants, NN12 8TN Tel. 01327 858400

1.3 Competitor Eligibility:

1.3.1 Entrants must:

- I be fully paid-up members of the HSCC and
- II be Registered for the Series and
be in possession of a valid Motorsport UK Entrant's Licence.

1.3.2 Drivers and Entrant/Drivers must:

- I be current Members of the HSCC and
- II be registered for the Series © and
- III be in possession of a valid Competition (Racing) Club status Licence, *as a minimum*
*Or be in possession of the highest grade of national Race licence or valid FIA International Licence, , including confirmation of a valid medical certification, together with their ASN's written consent FIA ISC Article 2.3.7 applies)

PUBLISHED REGULATIONS

- 1.3.3 Additionally, If participation in the Series requires absence from education a driver, in full time school education is required to have the approval of their head teacher and a letter stating such approval from their school in order to fulfil registration for the series. A driver shall not take time out of their education to participate in motor sport without the prior written approval of their education establishment.
- 1.3.4. All competitors must sign-on at Events that they compete in and all necessary documentation must be available to be presented for checking at all times upon the demand of the Officials.

1.4 Registration:

- 1.4.1 All competitors must register for the Series via the online membership registration process at www.hsc.org.uk prior to the Final Closing date for the first round being entered.
- 1.4.2 The Series Registration form is available from www.hsc.org.uk prior to the Final closing date for the first event being entered.
- 1.4.3 The membership year runs from 1st January to 31st December. Registrations will be accepted from 1st January in the membership year.
- 1.4.4 Registration numbers will be the permanent Competition numbers for the Series season and issued by the organisers on a first come, first serve basis.

1.5 105 Cup© Events:

The Series events are as follows:

| Date | Circuit | Status | Org. Club |
|---------------|--|-----------|-----------|
| 26 April | Snetterton 200 | Interclub | HSCC |
| 31 May | Donington Park | Interclub | HSCC |
| 13-14 June | Cadwell Park | Interclub | HSCC |
| 11-12 July | Legends of Brands Hatch GP | Interclub | HSCC |
| 25-26 July | Silverstone Classic | Interclub | HSCC |
| 9 August | Castle Combe HSCC 60 th Anniversary | Interclub | HSCC |
| 29-31 August | Oulton Park Gold Cup | Interclub | HSCC |
| 10-11 October | Silverstone Finals | Interclub | HSCC |

1.6 Awards:

- 1.6.1 All awards are to be provided by the race organisers.
- 1.6.2 Awards will be given to 1st in each class, subject to two or more starters in the class.
- 1.6.3 1st in each class will receive a trophy, the 105 GT Cup, 105 GTV Cup or the 105 GTA Cup
- 1.6.4 **Presentations:** Awards are to be provided for presentation at the end of each race or at the end of the meeting presentation ceremony. All competitors are expected to attend.
- 1.6.5 **Entertainment Tax Liability.**
Prize money and Bonuses are not applicable at HSCC events.
- 1.6.6 **Title to all trophies/awards:**
If Provisional Results are revised after the presentation of any awards and such revisions affect the entitlement to those awards, the Competitor(s) concerned must return them to the Organisers in good condition within 7 days of them being requested to allow them to be reallocated.

2. SERIES EVENT MEETINGS & RACE PROCEDURES

2.1 Entries:

- 2.1.1 Competitors are responsible for registering correct and complete entries with the correct entry fee prior to the closing date for entries before each event.
- 2.1.2 Incorrect or incomplete entries (including Driver to be Nominated Entries) are to be held in abeyance until they are complete and correct and the date of receipt for acceptance of entry purposes shall be the date on which the Secretary of the Event receives the missing or corrected information or fee.
- 2.1.3 Any withdrawal of Entry or Driver/Car changes made after acceptance of any entry must be notified to the Event Organisers in writing NCR Ch.3 App.11 Art.1.1 applies
- 2.1.4 The Entry Fee for each event shall be specified in the SRs and on the entry form.
- 2.1.5 Reserves will be listed in the Final List of Entries published with Final Instructions or in a Bulletin.

2.2 Briefings:

Organisers must notify Competitors of the times and locations for all briefings in the Final Instructions for the Events. Competitors must attend all briefings. Any Written briefing is an Official Document.

2.3 Qualification Practice:

- 2.3.1 Should any Practice Session be disrupted, the Clerk of the Course shall not be obliged to resume or re-run the session; the decision of the Clerk of the Course shall be final.
- 2.3.2 Each driver shall complete a minimum of 3 laps in the car to be raced, and in the correct session, in order to qualify. (NCR Ch.12.App.6 Art.3.2.)
- 2.3.3 If there is more than one race at a race meeting, the grid position for Race 2 will be set by the finishing order of Race 1.

2.4 Races:

Should any race be disrupted the Clerk of the Course shall not be obliged to resume or rerun the race . (NCR Ch.12 App.6 Art.9.1)

2.5 Starts:

- 2.5.1 All cars will be released to form up on the grid prior to the start in formation as specified on the grid sheet.
- 2.5.2 The start will be either via a Standing start unless otherwise stated in the event Final Instructions.

Standing Start

The minimum Countdown procedures/audible warning sequence shall be:-

- I 1 minute to start of Green Flag Lap – Start Engines/Clear Grid
- II 30 Seconds – Visible and audible warning for start of Green Flag/Pace Lap.
- III After completion of the Green Signal Lap vehicles will resume their Grid positions for a standing start.
- IV A five second board will be used to indicate that the grid is complete.
- V The red lights will be switched on five seconds after the board is withdrawn and switched off to indicate the start of the race.

- 2.5.3 Any car removed from the grid after the one minute signal or driven into pits on Green Flag Lap shall be held in the pitlane and may start the race after the last car has passed the Startline or pitlane exit, whichever is the later.
- 2.5.4 Any driver unable to start the Green Flag/Pace Lap or start is required to indicate their situation as per NCR Ch.12 App.6 Art.6.11. In addition, any driver unable to maintain grid position on Green Flag Lap, to the extent that ALL other cars are ahead of them, may complete the green flag lap but MUST remain at the rear of the last row of the grid but ahead of any cars to be started with a time delay.
- 2.5.5 In the event of any starting lights failure the Starter will revert to use of the National Flag.
- 2.5.6 Should circumstances at the event change such as, but not restricted to, Track Conditions or Weather, the Clerk of the Course may change Standing Starts to Rolling Starts. When this decision is made all affected competitors will be notified at the earliest opportunity with a briefing note to advise the Rolling Start procedure along with being advised of the number of Pace laps.

2.6 Session Red Flag

Should the need arise to stop any race or practice, Red Light Panels/Flags will be switched on at the Startline and RED FLAGS will be displayed at the Startline and at all Marshals' Signalling Points around the circuit.

This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the pitlane during practice and to the starting grid area during a race, unless otherwise directed by officials. **Marshals** should revert to displaying yellow flags to indicate to Drivers the particular location of any incident hence supplementing the Light Panels.

Vehicles should not enter the Pits unless directed to do so and all cars in the pit lane during a red flag period must take any restart from the pit exit.

2.7 Pits, Paddock & Pitlane Safety:

- 2.7.1 **Pits & Paddock:** Competitors must ensure that the Motorsport UK, Circuit Management and Organising Club Safety regulations are complied with at all times.
- 2.7.2 **Pitlane:** The outer lane or lanes are to be kept unobstructed to allow safe passage of cars at all times. The onus shall be on all drivers to take all due care and respect the pitlane speed limits.
- 2.7.3 **Refuelling:** May only be carried out in accordance with the NCR 12.11.27, Circuit Management Regulations and the Supplementary Regulations or Final Instructions issued for each Circuit/Event.
- 2.7.4 **Speed Limit:** Pitlane Speed Limit will be 60 Km/h (37.2Mph). You are classed as being in the pitlane once the front wheels of the car have crossed the pit entry line and you must not exceed the Pitlane Speed Limit until the front wheels have crossed the pit exit line. Pitlane speed limiters are permitted. Failure to comply with the speed limit may result in the imposition of the following penalties **for each Km/h over the Pitlane Speed Limit:**
Races: A minimum fine of £10 and/or a one-second race time penalty.

2.8 Race Finishes:

To be classified as a finisher, only vehicles that have covered at least 80% of the distance covered by the class winner and which cross the finishing line (not in the pit lane) under their own power and within four minutes after the overall winner will be classified in the Provisional result. Should this percentage not result in a full number of laps the decimals will be disregarded.

After taking the Chequered Flag drivers are required to:

- I progressively and safely slow down,
- II remain behind any competitors ahead of them,
- III return to the Pitlane Entrance/Paddock Entrance as instructed,
- IV comply with any directions given by Marshals or Officials
- V keep helmets on and harnesses done up while on the circuit or in the pitlane.

2.9 Results:

All Practice Timesheets, Grids, Race Results are to be deemed PROVISIONAL until all vehicles are released by Scrutineers after Post Practice/Race Scrutineering and/or after completion of any Judicial or Technical Procedures. {NCR Ch3.App6.Art.1.4}.

2.10 Timing Modules:

All cars must be fitted with a working transponder compliant with the timekeeper's equipment. Failure may result in competitors not being accredited with a qualifying time or being disqualified from the result as per NCR Ch12.App6.Art.2.2

No electronic equipment may be placed within five meters of any official timing line and any breach of this may result in the confiscation of the equipment concerned.

2.11 Qualification Races:

If any event is oversubscribed the Organising Club may, at its discretion, run Qualification Races.

2.12 Operation of Safety Car:

The safety car will be brought into operation and run in accordance with NCR Ch.12 App.8 Art.2

2.13 Onboard Cameras:

The use of onboard cameras is compulsory and they must be fitted at scrutineering for examination. Upon request any onboard footage must be made available to Clerk of the Course and or Stewards. Ch.7 App.9 applies. Please ensure that SD cards are regularly cleared to assist Clerks with identification and review of relevant footage.

2.14 Lap Timing & Data Logging

The use of linked data performance loggers that supply real time information in cockpit are not permitted.

The use of data loggers that record data for post-race analysis are accepted.

3. SPECIFIC 105 Cup© REGULATIONS

- 3.1 By registering for the series all competitors and their associates commit to positively promote and demonstrate the Motorsport UK's Respect Code which is appended to these regulations (Appendix 4).
- 3.2 Where any reports of disrespectful conduct are judged to be well founded the Series organisers may issue warnings or require remedial actions which can include race bans through referral to Motorsport UK
- 3.3 It is imperative that we promote the safety and wellbeing of young people and adults at risk. In addition to this all participants must be aware of their behaviour and conduct at all times and abusive language and harmful behaviour will not be tolerated. Any such incidents must be reported to the 105 Cup© Coordinator and/or Safeguarding Officer who will also relay the report Motorsport UK. Details of the Motorsport UK Policies and Guidelines are available at www.motorsportuk.org/resource-centre by selecting Policies and Guidelines.

4. SPECIFIC SERIES PENALTIES:

In accordance with NCR Chapter 2 and these Series Regulations

Infringements of Technical Regulations:

- 4.1.1. Arising from post practice Scrutineering or Judicial Action:
Minimum Penalty: The provisions of NCR Ch.2.App.8.Art.1.21.
- 4.1.2. Arising from post race Scrutineering or Judicial Action:
Minimum Penalty: Disqualification from the Race.

4.2 Table of Penalties

| Offence | NCR Reference | Penalty | Licence Penalty Points |
|---|---|--|-----------------------------|
| Abusive language or behaviour | Ch.2 App. Art.1.1. | Session Disqualification | ✓ Ch.2 App.12 Art.1.2.c. |
| Actual Assault or threat of physical assault or particularly aggressive behaviour | Ch.2 App.1 Art.1.1 | Event Disqualification + Consideration of Licence suspension (30 days) | ✓ Ch.2 App.12 Art.1.2.c. |
| Failure to obey the instruction of an official | Ch.6 App.1 Art.2.4 | Qualifying: Fine Race: Grid Penalty | ✓ Ch.2 App.12 Art.1.2.d. |
| Causing a collision, repetition of serious mistakes or the appearance of a lack of control of the car | Ch.12 App.7 Art.1.8 | Qualifying: Grid Penalty Race: Time / Place Penalty | ✓ Ch.2 App.12 Art.1.2.a. |
| Causing another competitor to leave the circuit, crowding to inside or outside of the track | Ch.12 App.7 Art.1.5 | Qualifying: Grid Penalty Race: Time / Place Penalty | ✓ Ch.2 App.12 Art.1.2.a. |
| Excessive weaving to prevent an overtaking move | Ch.12 App.7 Art.1.5 | Qualifying: Grid Penalty Race: Time / Place Penalty | ✓ Ch.2 App.12 Art.1.2.a. |
| Gaining Unfair Advantage | Ch.2 Ann.A, Art.1.3. | Qualifying: Loss of lap time(s) Race: Time / Place Penalty | ✗ |
| Incompatible with general safety | Ch.2 App.1 Art.1.13 | Disqualification (session or event) | ✓ Ch.2 App.12 Art.1.2.a. |
| Failing to observe the Chequered Flag (taking the flag more than once) | Ch.12 App.8 Art.1.7 Ch.2 App.1. Art.1.14. | Verbal Warning | ✓ Ch.2 App.12 Art.1.2.b. |
| Not obeying the Black Flag | Ch.12 App.8 Art.1.7 Ch.2 App.1. Art.1.14. | Disqualification | ✓ Ch.2 App.12 Art.1.2.b. |
| Not obeying the Black / Orange Flag | Ch.12. App.8 Art.1.7 Ch.2 App.1. Art.1.14. | Qualifying: Loss of lap time(s) Race: Disqualification | ✓ Ch.2 App.12 Art.1.2.b. |
| Overtaking or not slowing down under yellow signals (Between the signal & the incident) | Ch.12 App.8 Art.1.7 Ch.2 App.1. Art.1.14. | Disqualification | ✓ Ch.2 App.12 Art.1.2.b. |
| Overtaking or not slowing down under yellow signals (After incident but before green) | Ch.12 App.8 Art.1.7. Ch.2 App.1. Art.1.14. | Qualifying: Loss of lap time(s) Race: Time / Place Penalty | ✓ Ch.2 App.12 Art.1.2.b. |
| Safety Car: Overtaking or overlapping another competitor | Ch.12 App.8 Art. 2.6 Ch.2 App.1. Art.1.14. | Time Penalty | ✓ Ch.2 App.12 Art.1.2.b. |
| Safety Car: Overtaking of the safety car | Ch.12 App.8 Art.2.6 Ch.2 App.1. Art.1.14. | Lap / Place penalty | ✓ Ch.2 App.12 Art.1.2.b. |
| Failing to attend a drivers' briefing | Ch.6 App.1 Art.2.3 (Ch.5 Part 1 App.5 Art.2.3h) & Ch.1 App.2 Art.11.6.i.) | Fine | ✗ |
| Making a false start | Ch.12 App.6 Art.7 | Time Penalty: 10 sec | ✗ |

| | | | |
|--|-----------------------|---|-----------------------------|
| Reversing in the pit lane or on track | Ch.12 App.7 Art.1.12. | Qualifying: Grid penalty Race: Drive through penalty | ✓ Ch.2 App.12 Art.1.2.a. |
| Running beyond the track limits in qualifying | Ch.12 App.7 Art.1.6 | Loss of lap time(s) [specify the relevant lap time concerned not just the fastest] | ✗ |
| Running beyond the track limits in racing | Ch.12 App.7. Art.1.6. | Scale of penalty set out in NCR Ch.12 App.7 Art.1.11.b. | ✗ |

| Safety/Technical Offence | NCR Reference | Minimum Penalty |
|---|---|---|
| Breach of a safety regulation: (Fire extinguisher pin, Fuel sample connector or similar) | Ch.5 App.5 Art.2.3a) | Fine |
| Failing to advise the Clerk of impending eligibility check | Ch.2 App.8 Art.1.7 | Fine |
| Fuel or tyres do not conform to regulations | Ch.8 App.0 Art.1.8 Ch.8 App.2 Art.1.4 | Disqualification from session (plus, any Championship Penalties) |
| Incorrect or unreadable numbers, incorrect missing or misplaced decals | Ch.7 Art.10 Ch.12 App.4 Art.5 | Fine |
| Ineligible or unsafe vehicle at pre-event scrutineering | Ch.5 App.5 Art.2.3 Ch.2 App.8 Art.1.21 | Start refused |
| Ineligible or unsafe vehicle after practice / qualifying | Ch.5 App.5 Art.2.3 Ch.2 App.8 Art.1.21 | Disqualification |
| Ineligible or unsafe vehicle after even | Ch.5 App.5 Art.2.3 Ch.2 App.8 Art.2 | Disqualification (+ Championship Penalty) |
| Scrutineering: False declaration in pre-event paperwork, including those about PPE | Ch.2` App.1 Art.1.11. | Before going on track: Fine (+ must rectify) Been on track: Disqualification |
| Breach of Parc Ferme | | Disqualification |

5. TECHNICAL REGULATIONS

5(1) INTRODUCTION:

The following Technical Regulations are set out in accordance with the National Competition Rules specified format and it should be clearly understood that if the following texts do not clearly specify that you can do it you should work on the principle that you cannot.

If you are in any doubt check with the Eligibility Scrutineer.

The Technical regulations (section 5) must be read in conjunction with the Class Specific Appendix 1, 2 & 3.

5(2) GENERAL DESCRIPTION:

Eligible Cars:

The HSCC 105 Cup© is for competitors participating in genuine production Alfa Romeo 105 Saloons, Spiders and Coupes built or road-registered between 1/1/63 and 31/12/77

It is the intention of the regulations that the appearance of cars should remain as close to original as possible.

The HSCC 105 Cup© Organisers may classify, reclassify or disqualify any car following referral by the Eligibility Scrutineer.

All cars must have an approved and current HSCC Vehicle Identity Form (VIF) **or** an FIA HTP **or** an HRDC Historic Race Passport .

The issuance of a Vehicle Identity Form (VIF) or equivalent does not confirm eligibility or acceptance into the HSCC 105 Cup©. All documentation must be available at events entered, produced at scrutineering and when required at post-event checks.

For the purpose of these technical regulations, the term manufacture or manufacturer refers to the manufacturer of the vehicle unless clearly specified otherwise.

Chassis is defined to mean a chassis to which bodywork and mechanical components are fixed or a unitary monocoque bodyshell.

Presentation:

At the start of each free practice, qualifying session or race, the cars must be presented to a high standard and must be clean and in good order. The Organisers reserve the right to forbid cars not meeting this requirement from taking part. Non-period colour schemes, unpainted panels, dents and scrapes are not acceptable.

Class Structure of 105 Cup©:

The Series will be run in three classes as follows:

Class A - GT – for cars up to 1600cc compliant with Appendix 1 of the 105 Cup Regulations.

Class B - GTV - for cars up to 2000cc compliant with Appendix 2 of the 105 Cup Regulations

Class C - GTA – for cars up to 2000cc compliant with Appendix 3 of the 105 Cup Regulations

Class D - Invitation – For vehicles approved by the committee not conforming to the Regulations

5(3) **SAFETY REQUIREMENTS**

5(3).1 The following sections of the NCRs will apply:

- NCR Ch.7 Competitor Vehicles & Vehicle Safety Equipment
- NCR Ch.12 (Circuit Racing)

NCR Ch.7 App.4 Art.3 Crushable Structures which do not apply.

5(3).2 NCR Ch.7.App.3 Roll Over Protection Systems (ROPS) are mandatory and are permitted only in the configurations outlined and shown in drawings in the Motorsport UK Technical Notes. ROPS must not become a chassis extension (See 5(5).2). Further advice on ROPS can be obtained from the 105 Cup© Eligibility Scrutineer or HSCC Chief Scrutineer.

For the avoidance of doubt a total of 8 ROPs and 2 SIPs points (10 in total) are allowed.

5(3).3 NCR Ch.7 App.7 Art.1 -2 & NCR Ch.7 App.7 Art.5 -9 Seats, seat belts and harnesses must comply with this regulation.

5(3).4 NCR Ch.7.App.6. Plumbed-in fire extinguishers are mandatory

5(3).5 NCR Ch.7 App.5 Art.6 A rearward facing red warning light is mandatory and must comply with this regulation.

5(3).6 NCR Ch.7 App.4 Art.2 Tank Fillers, Vents and Caps must comply with this regulation.

5(3).7 Glass sun-roofs are not permitted.

5(3).8 NCR Ch.7 App.5 Art.5 An External Circuit Breaker is mandatory and must comply with this regulation.

5(3).9 NCR Ch.9 & Ch.12 Racing overalls are mandatory and must comply with this regulation.

5(3).10 Crash helmets are mandatory and must comply with NCR Ch.9 & Ch.12. Either goggles or a visor must be worn unless in a closed vehicle NCR Ch9. App11).

5(3).11 All other race clothing must comply with Motorsport UK requirements-NCR Ch. 9 and NCR Ch.12 App.12Art.1

5(3).12 The use of HANS devices is compulsory

5(4) **GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS:**

5(4).1 Vehicle Identity Papers

All vehicles must comply with their HSCC Vehicle Identity Form (VIF) or FIA HTP or HRDC Historic Race Passport, Technical Regulations in **NCR Ch.12.App.13** including the Safety Requirements of NCR Ch.7. The driver must ensure the VIF is available at scrutineering and throughout each day of each event they attend.

5(5) **CHASSIS:**

5(5).1 The Chassis must remain as original with no additions or removals, except fixings for ROPS as required NCR Ch.7 App.3 It is not permitted to attach the ROPS to the chassis at any additional points. The maximum number of attachment points permitted is 8 and these must be at the location of the feet fitted by the ROPS manufacturer. It is NOT permitted to weld the ROPS to the bodyshell at any other points see NCR Ch.7.App.13 Diagram 45). It is NOT permitted to attach the ROPS to suspension turrets NCR Ch.7.App.13 Diagram 20. Where the chassis has been the subject of structural repair, the repair will be subject to approval by the Eligibility Scrutineer.

5(6) BODYWORK:**5(6).1 General**

No modifications from original production specification are permitted, except where specifically allowed.

Body panels attached with nuts, bolts or rivets can be replaced with panels of different material such as aluminium or fibreglass.

Permission must be obtained from the Eligibility Scrutineer prior to any modifications being made.

5(6).2 Interior

It is permitted to remove passenger seat and floor carpets but if the passenger seat is retained it must be rigidly secured.

Cars will be expected to retain their original type of trim in so far as it relates to fixed portions (e.g. door trim, dashboard trim etc.).

Wooden dashboards may be replaced by other non-structural material. Non original racing style seats may be fitted in place of the standard seats.

5(6).3 Exterior

Factory option hard tops are allowed. Open cars fitted with a front roll-bar hoop must practice and race with hardtop fitted or with their hood erected.

Bumper bars and brackets may be removed.

Side and rear window glass may be replaced by Perspex or similar material no less than 4mm thick.

Closed vehicles must have an effective means of ventilation.

The silhouette of the car must not be altered, (except for safety equipment or minor amendments subject to individual acceptance by the Eligibility Scrutineer) and brake cooling ducts (See 5(11).3).

Original outer door handles must be fitted and working.

No aerodynamic aids are permitted

5(6).4 Ground Clearance

All Classes may be lowered but all sprung parts of the car must have a minimum ground clearance with the driver seated normally of 10cm, such that a block of 8cm x 8cm x 10cm high or a suitable roller 10cm in diameter may be passed along any route underneath the car. Ground clearance may be measured at any time during an event, on a surface specified by the HSCC Eligibility Scrutineer. Exhaust systems, outer lower suspension pickup points, all lower anti-roll bar mountings and bolts required to attach safety equipment are excluded from this requirement.

5(7) ENGINE**5(7).1 General**

The car must be fitted with an Alfa Romeo 8v single spark Nord engine up to 2000cc. It does not have to be the original engine the car was built with, but no modifications from original production specification to the engine installed and declared (1290cc, 1570cc, 1779cc, 1962cc) are permitted unless stated.

The engine must be mounted in the original manufacturer's position within the vehicle. The engine, cylinder head and block must be the original manufacturer's make, type, material, stroke, and date from the same period as the vehicle model was produced.

5(7).2 Permitted Modifications

Cylinder heads may be polished, ported and re-profiled.

Camshafts are free. Camshaft drive method must be as original manufacturer.

Valves are free.

Pistons are free.

Con-rods are free.

Crankshafts are free but must retain the original manufacturer stroke.

Flywheels are free.

Re-boring is permitted to a maximum oversize of 0.060 in. of the manufacturer bore size without affecting the capacity class of the vehicle.

5(7).3 **Location**

The engine location must be in the original position when the car was manufactured and use original mounting points.

5(7).4 **Oil/Water Cooling**

Oil coolers are permitted but with no external ducting.

Aluminium water radiators and electric fans are permitted; the fans must not protrude beyond the radiator opening. Radiators must be mounted in the original manufacturer's position.

Water pump must be fitted in the original manufacturer position and driven by manufacturer method. Water pump impeller size is free.

5(7).5 **Induction Systems**

All induction systems must be the original manufacturer standard fitment. No forced induction is permitted.

Carburettors must be of the same size and number as original specification and be mounted directly onto the original inlet manifold which may be polished and ported.

Weber DCOE carburettors may be replaced by the equivalent DHLA Dellorto and vice versa.

Fixed choke dimensions must be as original. Detachable choke tubes dimensions must be as original manufacture for that production car. Jet, needle size and springs are free. Evidence of original size at manufacture must be provided by the competitor to the Eligibility Scrutineer.

Cars fitted with fuel injection must use the original manufacturer-standard fitment fuel injection system, including throttle body.

5(7).6 **Exhaust Systems**

The exhaust manifold and system is free, but must comply with NCR 7.8 and also subject to individual circuit requirements if specified in Supplementary Regulations.

5(7).7 **Ignition Systems**

The ignition system must be to the original manufacture specification including the distributor and retain the original manufacturer firing order. It is permissible to fit a basic/simple electronic ignition system solely as a means of replacing contact breaker points. In such systems the distributor must remain the sole means of triggering the spark.

5(7).8 **Fuel Systems**

Tanks: The fuel tank must be either the original production specification, or a safety tank. Any fuel tank must comply with FIA Appendix K Art. 5.5, and must not exceed the originally specified capacity.

Locations: Fuel tank must be in the original manufacturer location or within the luggage compartment, if that space is separated from the cockpit by a sealed fire-resistant firewall. Installation must comply with Motorsport UK Technical Regulations (e.g Ch.7.App.1.4)

Fuel: Only petrol as defined in NCR Ch.8 App.1 Art.1.7 and complying with BS4040, BSEN228 or BS7800 may be used; fuel which exceeds the stated RON (max) levels in NCR Ch.8 App.1 Art.1.7 is **prohibited even if it is sold/promoted as being legal for UK Competition** and/or obtainable from 'roadside' pumps. The use of additives by competitors which boost the octane rating (RON) in any

petrol is prohibited. At the end of practice and the race at least 3 litres of petrol from the tank of the competing car must be available to the scrutineers for analysis. Compliance with minimum weight for the car will be taken before the petrol is removed.

Delivery: Pumps, filters, and regulators are free. Use of braided flexible hose and metal fuel lines is recommended.

5(8) SUSPENSIONS

- 5(8).1 The front and rear suspension must be as original manufacturer, except it may be strengthened for safety reasons with the approval of the Eligibility Scrutineer.
- 5(8).2 Standard manufacturer mounting points must be used for fitting suspension arms and shock absorbers.
- 5(8).3 Shock absorbers and springs may be changed. It is not permitted to use remote reservoirs.
- 5(8).4 Single tube, adjustable shock absorbers are permitted and must be fitted to the original manufacturer's mounting points. Remote reservoirs are not permitted. Adjustable spring platforms are permitted.

Anti-roll bars sizes are free and may be adjustable. They may be fitted to the front and rear suspension if not fitted in original manufacture.
- 5(8).5 a Watts linkage may be fitted
- 5(8).6 Original bush material may be changed.
- 5(8).7 Spherical joints are not permitted on any suspension components unless used in original manufacture except as follows:-
- 5(8).8 Anti-roll bars may be fitted with spherical joints provided they do not affect the geometry.
- 5(8).9 Watts linkage fitted under regulation 5(8).5 may be fitted with spherical joints to mount to the chassis and axle.
- 5(8).10 Telescopic shock absorbers may use spherical bearings but must be fitted to manufacturer mounting points
- 5(8).10 Camber alterations are permitted.
- 5(8).11 It is permitted to fit roller bearing top mounts to strut suspension
- 5(8).12 Front and rear bolt-in suspension strut braces are allowed
- 5(8).12 Wheelbase to be to manufacturer specification for all cars.

5(9) TRANSMISSIONS

5(9).1 Gearbox/Clutch

No modifications to original production specifications are permitted except brass/bronze components used in gearbox internal components may be changed for steel to identical dimensions.

Clutch pressure plate and driven plate are free.

The clutch control system method can be either cable, rod or hydraulic. Hydraulic clutch master cylinder is free.

Concentric slave cylinders are not permitted unless fitted as original manufacturer equipment.

It is permitted to change a carbon thrust release bearing to a roller bearing on the manufacturer carrier.

Straight cut gears are not permitted.

5(9).2 Final Drive

The rear axle must of a type originally available as standard or as an option for the car.

The final drive ratio is free.

Limited slip or torque biasing differentials are permitted.

5(10) ELECTRICS

5(10).1 All electrical equipment and exterior lighting fitted in original manufacture must be retained (except as listed below) in the original location, and fully operational; wiring may be changed but electrical equipment must still comply with MOT requirements.

5(10).2 **Batteries:** The type, make, capacity (ampere-hours) and location of the battery are free except that lithium batteries are not permitted. Battery mounting must be in accordance with.NCR 7. Appendix 5.1 Batteries

5(10).3 **Generators/Alternators:** The type and make are free. Dynamos may be replaced by alternators, but must be in the original position. The dynamo or alternator must generate an electric output and be on load when the engine is running.

5(10).4 Starter motors are free.

5(10).5 **Headlights:** All cars must have a minimum of two working headlights with main and dip beam. Those cars built with four headlights may convert to two headlights providing they retain the main/dip beam function.

5(11) BRAKES

5(11).1 Hydraulic braking systems may be converted to dual circuit operation which provides simultaneous operation on all four wheels via two distinct hydraulic circuits. Hydraulic lines may be replaced with metal braided type piping.

5(11).2 It is not permitted to fit grooved, cross-drilled, ventilated or otherwise modified discs, unless fitted as original. Discs and drums must be of the material and dimensions originally specified. Brake calipers must be original production items for the model car, made of original materials and to original dimensions.

5(11).3 It is permitted to fit brake cooling ducts but these must not protrude more than 2cm outside the bodywork and must blend with the surrounding bodywork. ~~and~~ No ducting hoses must be visible externally.

5(11).4 Adjustable brake devices are permitted but must not be accessible or adjustable by the driver when the car is in motion.

5(12) WHEELS/STEERING

5(12).1 Wheels

Wheel diameter is free up to a maximum of 15".

Rim width may be up to 6".

The same size wheels must be used front and rear.

The wheel and tyre must be capable of being used within standard bodywork and permitted suspension modifications. Rim widths may need to be decreased in order to accommodate available tyres.

Alloy wheels of period design are permitted subject to individual acceptance by the Eligibility Scrutineer.

5(12).2 Steering

The steering rack/box and column must be standard manufacturer specification. The steering lock must be rendered inoperative or removed, except in road driven vehicles
Steering wheel is free. Removable type is recommended.

5(13) TYRES

- 5(13).1 Only tyres from the NCR Ch.8. App4 Art.1 list 1A/1B/1C are permitted unless a car complies with FIA App K regulations in which case Dunlop CR65 L or M section in 204 compound may be used.
- 5(13).2 The same size tyres must be used front and rear, unless varied in original manufacture. The same type and compound of tyres must be used front and rear.
- 5(13).3 Tyres must have a minimum of 50 profile.
- 5(13).4 The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.

5(14) WEIGHTS

- 5(14).1 Minimum weights for each class are listed in Appendix 1, 2 and 3 of these regulations
- 5(14).2 Ballasting is permitted, which if used must be securely affixed to the vehicle as per sections. NCR Ch.7 App.2 Art.19 Lightening cars then adding ballast to meet the minimum weight is not acceptable.
- 5(14).3 Weights of individual cars may be verified by the Eligibility Scrutineer at circuit weigh-bridges in accordance with the National Competition Rules.

5(15) NUMBERS AND 105 Cup© DECALS

- 5(15).1 Numbers must be displayed as per NCR Ch.7 App.13 Diagram 1 Competitions Numbers. It is a competitor's responsibility for the competing vehicle to be easily identified by all course officials.
- 5(17).2 Advertising on vehicles must comply with sections NCR Ch.6 App.1 Art.8 & NCR Ch.6 App.1 Art.9
- 5(17).3 All competing cars must display two HSCC badges, two 105 Cup© logos, one on each side of the car, towards the front and near the top of the front door; alternatively, if insufficient space available, at the rear and near the top of the front wings on a near vertical surface.

The 105 Cup© logo to be placed in line with and immediately below the HSCC badge.

6. APPENDICES

The following Commercial Undertakings are not subject to the judicial procedures of either the Championship Stewards and/or the Motorsport UK /MSC.

6.1 Race Organising Clubs and Contacts:

HISTORIC SPORTS CAR CLUB: Silverstone Circuit, Silverstone, Towcester, Northants, NN12 8TN
(T) 01327 858400 (F) 01327 858500 email: office@hsc.org.uk
Website: www.hsc.org.uk

Licensed Eligibility Scrutineer: **Jeff Nixon**
Championship Chairman: **James Nairn**

APPENDIX 1

This appendix is specific to 105 GT class cars only

The following changes to the 105 Cup© regulations shall be permitted for cars racing in the 105 GT class:

- The minimum weight limit shall be 920kg
- The Maximum carburetor size shall be 45mm and choke size is free
- Fuel Tank size is free but the car must be able to complete a 45 minute race without the need to refuel

Cars shall be weighed at the end of a qualifying session or race in the trim they come off the track in excluding the driver and his personal gear (helmet, HANS etc).

For the avoidance of doubt all other 105 Cup© regulations shall apply.

APPENDIX 2

This appendix is specific to 105 GTV class cars only

The following changes to the 105 Cup© regulations shall be permitted for cars racing in the 105 GTV class:

- The minimum weight limit shall be 912kg (The 70's RoadSports permitted weight)
- The maximum carburetor size is 40mm, choke size shall be as originally fitted by the manufacturer

Cars shall be weighed at the end of a qualifying session or race in the trim they come off the track in excluding the driver and his personal gear (helmet, HANS etc).

For the avoidance of doubt all other 105 Cup© regulations shall apply.

APPENDIX 3

This appendix is specific to 105 GTA class cars only

The following changes to the 105 Cup© regulations shall be permitted for cars racing in the 105 GTA class:

- The minimum weight limit shall be 873kg (90% of the 2000 GTV Homologated weight)
- There shall be no limit to maximum carburetor or choke size
- Gear ratios are free provided they are the same helical design as original and fit within the factory casing. The same number of forward and reverse gears must be retained
- Spherical bearings allowed throughout
- Wheels up to 15" diameter and 7" width shall be permitted
- Brake calipers and discs are free
- Minimum ground clearance shall be 60mm
- Fuel Tank size is free but the car must be able to complete a 45 minute race without the need to refuel
- It is permitted to replace the mechanism of the distributor with either a basic electronic system in place of the points or with an aftermarket programmable solid state device provided it is driven by the same mechanism

Cars shall be weighed at the end of a qualifying session or race in the trim they come off the track in excluding the driver and his personal gear (helmet, HANS etc).

For the avoidance of doubt all other 105 Cup© regulations shall apply.

GTAm style cars shall be considered on a case by case basis before being allowed to race in the GTA class. For those which are permitted to race the following additional regulations will apply :

- Composite wheel arch extensions are permitted on GTAm evocation cars but this shall not extend to whole wings which must remain in steel
- Wheels up to 10" in width shall be permitted
- GTAm style cars shall meet the GTAm homologation weight of 920kg

APPENDIX 4

A socially-minded standard of behaviour is expected from everyone within the motorsport community.

By participating in a Motorsport UK event in any capacity you agree to follow the values of the Respect Code:

[Motorsportuk.org/racewithrespect](https://motorsportuk.org/racewithrespect)

#RaceWithRespect

The Values

- Respect
- Fair play
- Integrity
- Good Manners
- Self-Control

I pledge to #RaceWithRespect and:

- Contribute to a welcoming and friendly environment that ensures the safety and welfare of all participants.
- Always behave with integrity and uphold fairness in the sport; play your part in keeping the sport safe through your actions
- Treat everyone with respect, regardless of their gender, ethnic or social background, language, religious or other beliefs, disability, sexual identity or other status
- Recognise that we all represent the sport and therefore have a duty to be polite and respectful to all staff, officials, fellow competitors, volunteers, as well as fans and supporters
- Respect the rules, regulations and authority of the officials and Motorsport UK

Any breach of these obligations may result in disciplinary action.

